


4203



Socket outlet with earthing contact and hinged cover USA/CANADA NEMA 5-20 R with screw terminals, Splash-protected flush-mounted IP44, white glossy

Technical features

Architecture

Fixing mode	flush-mounting
- 2pole + earth	

Main electrical features

Nominal voltage	125 V
Rated voltage	125 V AC
Frequency	50 Hz
Rated current	20 A

Cover, door

Cover	Central cover plate
-------	---------------------

Materials

Colour independent of design lines	white
Colour	white
Colour	white
RAL colour	RAL 1013 - Oyster white
Material	thermoplastic
Surface appearance	glossy

Dimensions

Insertion depth	19 mm
-----------------	-------

Installation, mounting

Installation mode	without spreader claws, for screw fastening
-------------------	---

Connection

Conductor cross-section (rigid)	max. 2 x 4 mm ²
- with screw terminals	

Use

Differentiation characteristic 3 - Sales	with screw terminals
--	----------------------

Standards

Standard	NEMA 5-20 R
----------	-------------

Safety

IK protection code against mechanical impacts	05
- without enhanced contact protection	

Identification

Application, usage	Flush-mounted wet-room installation
Main design line	Splash-protected flush-mounted IP44

Instructions

Information text

Not UL-certified.

- Only suitable for splash-protected IP44 flush-mounted installation when used in conjunction with the corresponding sealing set.
-