



## Blind actuator 12gang pro RMD 230 V KNX, light grey

### Technical features

#### Architecture

Bus system	KNX
Number of blinds/shutters outputs	12
Fixing mode	REG

#### Functions

Bus module detachable	no
Operating mode	operating mode can be set for roller shutter/awning
<ul style="list-style-type: none"> <li>- suitable to switch different external conductors</li> <li>- with sun shade function</li> <li>- with safety functions e.g. for wind, rain, alarm</li> <li>- with positioning function for blind and lamella position</li> </ul>	

#### Controls and indicators

Indicator lamp	yes
<ul style="list-style-type: none"> <li>- manual operation per channel using button (single-area operation)</li> <li>- Manual operation can be activated via selection switch, thereby deactivation of the KNX function</li> <li>- for activation of an AC drive per actuator channel</li> <li>- status LED integrated in the manual operation button</li> <li>- 6 manual operation buttons for up/down per channel/device</li> <li>- with illuminated programming button</li> </ul>	

#### Connectivity

Bus system radio frequent	no
Bus system LON	no
Bus system Powernet	no

#### Main electrical features

Type of supply voltage	AC
Frequency	50/60 Hz
Rated current	4 A

#### Voltage

Auxiliary voltage	230...240 V AC
Operating voltage over bus	21...32 V DC
System supply voltage	30V DC via bus

#### Electric current

Bus current consumption (data transfer)	7 mA
Bus current consumption (idle)	5 mA
Maximum switching current	4 A
Switching current at $\cos \varphi = 0.6$	max. 4 A

#### Materials

Colour	light grey
RAL colour	RAL 7035 - Light grey

75319010

IP20

### Dimensions

Depth	65 mm
Width of rail mounted device (RMD)	10 modules
Height	90 mm

### LED control

LED	Status LED integrated in manual operation button
-----	--

### Connection

Connection cross-sect. flexible conductor	0,5 / 6mm <sup>2</sup>
Connection cross-sect. rigid cable	0,5 / 6mm <sup>2</sup>
Conductor cross-section (flexible)	0,75...2,5 mm <sup>2</sup>
Conductor cross-section (flexible), without wire end sleeve	0,5...6 mm <sup>2</sup>
Conductor cross-section (rigid)	0,75...2,5 mm <sup>2</sup>
Type of connection	with screw
<ul style="list-style-type: none"> <li>- with integral bus coupling unit</li> <li>- with screw terminals</li> <li>- bus connection via connecting terminal</li> </ul>	

### Settings

Supported configuration modes	system
- switching time on change of direction adjustable	

### Scope of delivery

Bus connection included	yes
-------------------------	-----

### Equipment

Modular expandability	no
With slide for manual switch	yes

### Safety

Protection index IP	IP20
Halogen free	no

### Use conditions

Operating temperature	-5...45 °C
Storage/transport temperature	-20...70 °C

### Identification

Device family	TYM
Main design line	KNX