




75642002



## Universal interface 2gang flush-mounted with integral bus coupling unit, KNX

### Technical features

#### Architecture

Bus system	EIB
Fixing mode	flush-mounting

#### Functions

Bus module detachable	no
<ul style="list-style-type: none"> <li>- Switching functions, dimming functions, blind control functions functions, priority functions, scene functions, heating functions and timer functions</li> <li>- ETS additional functions: value transmitter 1 and 2 bytes, 2-channel mode, level switch function</li> </ul>	

#### Compatibility

- extension unit for light scene push-button

#### Controls and indicators

- with programming button and red programming LED

#### Connectivity

- with 2 independent binary inputs for potential-free contacts

#### Voltage

Input voltage	5 V
Input voltage	5 V
Operating voltage over bus	21...32 V DC
System supply voltage	30V DC via bus

#### Electric current

Number of entry circuits	2
Intensity by input	0,5 mA

#### Length

Max distance to switches	5 mm
--------------------------	------

#### Measurement

Input scanning voltage	per channel 5 V
------------------------	-----------------

#### Materials

Colour	light grey
Material	plastic

#### Dimensions

Dimensions (LLxwxh)	38 x 35 x 12 mm
---------------------	-----------------

#### Installation, mounting

Installation mode	for flush-mounted and hollow-wall mounting
-------------------	--

### Connection

Conductor cross-section (flexible)	0,75...2,5 mm <sup>2</sup>
Conductor cross-section (rigid)	0,75...2,5 mm <sup>2</sup>
Connection to	Potential free, switch, push button, automation system
<ul style="list-style-type: none"><li>- with integral bus coupling unit</li><li>- with pre-assembled cable</li><li>- bus connection via connecting terminal</li></ul>	

### Cable

Cable length extendable to	max. 5 m
----------------------------	----------

### Settings

Supported configuration modes	system, easy
-------------------------------	--------------

### Scope of delivery

Bus connection included	yes
-------------------------	-----

### Use

Differentiation characteristic 3 - Sales	with integral bus coupling unit
--	---------------------------------

### Safety

Protection index IP	IP30
Halogen free	no

### Use conditions

Operating temperature	0...45 °C
Storage/transport temperature	-20...70 °C

### Identification

Main design line	KNX
------------------	-----