



75316203



IP20

Heating actuator 6gang Triac RMD, 24 V/230 V AC with screw terminals, KNX, light grey

Technical features

Architecture

Bus system	KNX
Fixing mode	Din-Rail

Functions

- for 1 phase operation

Controls and indicators

- with programming button and red programming LED

Connectivity

Bus system radio frequent	no
Bus system LON	no
Bus system Powernet	no

Main electrical features

Frequency	50/60 Hz
-----------	----------

Voltage

Auxiliary voltage	110...230 V AC
Operating voltage over bus	21...32 V DC
Switching voltage	24...230 V

Electric current

Max. switching current (cos phi = 0.6)	1,5 A
--	-------

Power

Total power loss under IN	1 W
Power dissipation per coil	0,4 W

Materials

Colour	light grey
--------	------------

Connection

- with integral bus coupling unit
- bus connection via connecting terminal

Settings

Supported configuration modes	system
-------------------------------	--------

Scope of delivery

Bus connection included	yes
-------------------------	-----

Equipment

Modular expandability	no
Correcting variable consistent	yes
Correcting variable switching	yes
With slide for manual switch	yes

Use

Differentiation characteristic 3 - Sales	with screw terminals
--	----------------------

Safety

Protection index IP	IP20
---------------------	------

Use conditions

Operating temperature	-5...45 °C
Storage/transport temperature	-20...70 °C

Identification

Main design line	KNX
------------------	-----
