



41086062



**SCHUKO socket outlet with overvoltage protection with labelling field, Screw terminals, Berker
Q.1/Q.3/Q.7/Q.9, red velvety**

Technical features

Architecture

Design	according to DIN 49440
Fixing mode	flush-mounting

Controls and indicators

- with acoustic fault signal

Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

Voltage

Overvoltage protection	according to EN 61643 and VDE 0675-6-11
------------------------	---

Electric current

Rated current	16 A
---------------	------

Cover, door

Cover	Central cover plate
-------	---------------------

Materials

Design lines special colours	red
Colour	red
Colour	red
RAL colour	RAL 3003 - Ruby red
Material	thermoplastic
Surface appearance	velvety

Dimensions

Insertion depth	32 mm
-----------------	-------

Installation, mounting

Installation mode	with spreader claws
-------------------	---------------------

Connection

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
- with screw terminals	

Equipment

- with indicator LED for On/Error

Use

Differentiation characteristic 1 - Sales	with labelling field
Differentiation characteristic 3 - Sales	Screw terminals

Safety

IK protection code against mechanical impacts	05
Protection index IP	IP20
- without enhanced contact protection	

Identification

Main design line	Berker Q.1/Q.3/Q.7/Q.9
Secondary design line(s)	Berker Q.1, Berker Q.3, Berker Q.7, Berker Q.9

Instructions

Information text	Labelling field height arranged for P-touch strips 6 mm.
------------------	--