



6768813512



IP55



**Socket outlet with earthing pin and hinged cover surface-mounted enhanced contact protection, Berker W.1, polar white matt**

Technical features

**Architecture**

Fixing mode	surface-mounting
- 2pole + earth	

**Connectivity**

Type of USB port	other
------------------	-------

**Main electrical features**

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50 Hz
Rated current	16 A

**Cover, door**

Cover	Complete housing
-------	------------------

**Materials**

Colour of design line	polar white
Colour	polarwhite
RAL colour	RAL 9010 - Pure white
Material	thermoplastic
Surface appearance	matt

**Installation, mounting**

Installation mode	for screw fastening
-------------------	---------------------

**Connection**

Connection terminals	according to IEC 60884-1
- with plug-in terminals	

**Cable**

- with one entry for 2 cables and one entry for cable and tube
--

**Equipment**

- with full-face sealing on the rear side of housing for cable entry and surface adjustment on the backside
---

**Use**

Differentiation characteristic 2 - Sales	enhanced contact protection
--	-----------------------------

**Safety**

Enhanced contact protection	according to IEC 60884-1
Enhanced contact protection	according to VDE 0620-1:2021-02
- without enhanced contact protection	

**Use conditions**

---

Operating temperature	-40...30 °C
Storage/transport temperature	-50...50 °C

---

**Identification**

---

Main design line	Berker W.1
------------------	------------

---