



75010017



IP20

quickconnect

KNX Power supply 320 mA RMD with labelling field

Technical features

Architecture

Bus system	EIB
Fixing mode	REG

Connectivity

- one output 30 V DC, 320 mA incl. choke

Main electrical features

Frequency	50/60 Hz
-----------	----------

Voltage

Output voltage	28...32 V
----------------	-----------

Electric current

Output current	max. 320 mA
Output intensity	320 mA

Fuse

Fuse	with electronic short-circuit and overload protection
------	---

Materials

Colour	light grey
RAL colour	RAL 7035 - Light grey

Dimensions

Depth of installed product	64 mm
Height of installed product	90 mm
Length	64 mm
Width of installed product	72 mm

LED control

LED	with red LED for display of short-circuit and overload protection per output, with green LED for display of power supply
-----	--

Connection

Connection cross-sect. flexible conductor	0,75 / 2,5mm ²
Connection cross-sect. rigid cable	0,75 / 2.5mm ²
Conductor cross-section (flexible)	0,75...2,5 mm ²
Conductor cross-section (rigid)	0,75...2,5 mm ²
Connection	protected earth conductor must be connected
- with QuickConnect plug-in terminals	

Use

Differentiation characteristic 1 - Sales	with labelling field
--	----------------------

Safety

Protection index IP	IP20
---------------------	------

Use conditions

Operating temperature	-5...45 °C
-----------------------	------------

Storage/transport temperature	-20...70 °C
-------------------------------	-------------
