



47238907



**SCHUKO socket outlet with "ZSV" imprint enhanced contact protection, Berker S.1/B.3/B.7, orange**

Technical features

**Architecture**

Design	according to DIN 49440
Fixing mode	flush-mounting
Technical version	Imprint "ZSV"

**Connectivity**

Type of USB port	other
------------------	-------

**Main electrical features**

Nominal voltage	250 V
Rated voltage	250 V AC
Rated current	16 A

**Electric current**

Rated current	16 A
---------------	------

**Cover, door**

Cover	Central cover plate
-------	---------------------

**Materials**

Colour of design line	orange
Colour	orange
Colour	orange
RAL colour	RAL 2003 - Pastel orange
Material	duroplastic
Surface appearance	glossy

**Dimensions**

Insertion depth	32 mm
Installation depth, flush-mounted boxes	31 mm

**Installation, mounting**

Installation mode	with clamp/screw fastening
-------------------	----------------------------

**Connection**

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
- with plug-in terminals	

**Equipment**

With transparent product label holder	no
---------------------------------------	----

**Use**

Differentiation characteristic 2 - Sales	enhanced contact protection
--	-----------------------------

---

**Safety**

---

IK protection code against mechanical impacts	02
Protection index IP	IP20
Enhanced contact protection	according to IEC 60884-1
Enhanced contact protection	according to VDE 0620-1:2021-02
- Enhanced contact protection	

---

**Identification**

---

Main design line	Berker S.1/B.3/B.7
Secondary design line(s)	Berker S.1, Berker B.3, Berker B.7

---

**Instructions**

---

Information text	Insert colour-coded.
------------------	----------------------

---