




75644002



Universal interface 4gang flush-mounted with integral bus coupling unit, KNX

Technical features

Architecture

Bus system	EIB
Fixing mode	flush-mounting

Functions

Bus module detachable	no
<ul style="list-style-type: none"> - Switching functions, dimming functions, blind control functions, priority functions, scene functions, heating functions and timer functions - ETS additional functions: value transmitter 1 and 2 bytes, 2-channel mode, level switch function 	

Compatibility

- extension unit for light scene push-button

Controls and indicators

- with programming button and red programming LED

Connectivity

- with 4 independent binary inputs for potential-free contacts

Voltage

Input voltage	5 V
Input voltage	5 V
Operating voltage over bus	21...32 V DC
System supply voltage	30V DC via bus

Electric current

Number of entry circuits	4
Intensity by input	0,5 mA

Length

Max distance to switches	5 mm
--------------------------	------

Measurement

Input scanning voltage	per channel 5 V
------------------------	-----------------

Materials

Colour	light grey
Material	plastic

Dimensions

Dimensions (LLxwxh)	38 x 35 x 12 mm
---------------------	-----------------

Installation, mounting

Installation mode	for flush-mounted and hollow-wall mounting
-------------------	--

Connection

Conductor cross-section (flexible)	0,75...2,5 mm ²
Conductor cross-section (rigid)	0,75...2,5 mm ²
Connection to	Potential free, switch, push button, automation system
<ul style="list-style-type: none">- with integral bus coupling unit- with pre-assembled cable- bus connection via connecting terminal	

Cable

Cable length extendable to	max. 5 m
----------------------------	----------

Settings

Supported configuration modes	system, easy
-------------------------------	--------------

Scope of delivery

Bus connection included	yes
-------------------------	-----

Use

Differentiation characteristic 3 - Sales	with integral bus coupling unit
--	---------------------------------

Safety

Protection index IP	IP30
Halogen free	no

Use conditions

Operating temperature	0...45 °C
Storage/transport temperature	-20...70 °C

Identification

Main design line	KNX
------------------	-----