



47236003

# SCHUKO socket outlet with "SV" imprint enhanced contact protection, Berker Q.1/Q.3/Q.7/Q.9, green

**Technical features** 

| rcl |  |  |
|-----|--|--|
|     |  |  |
|     |  |  |
|     |  |  |

| Design            | according to DIN 49440 |
|-------------------|------------------------|
| Fixing mode       | flush-mounting         |
| Technical version | Imprint "SV"           |

## Connectivity

| Type of USB port | other |
|------------------|-------|
| Type of oob port | Other |

# Main electrical features

| Nominal voltage | 250 V    |
|-----------------|----------|
| Rated voltage   | 250 V AC |
| Rated current   | 16 A     |

## **Electric current**

| Rated current | 16 A |
|---------------|------|
|               |      |

## Cover, door

| Cover | Central cover plate |
|-------|---------------------|
|-------|---------------------|

## Materials

| Colour of design line | green                 |
|-----------------------|-----------------------|
| Colour                | green                 |
| Colour                | green                 |
| RAL colour            | RAL 6029 - Mint green |
| Material              | thermoplastic         |
| Surface appearance    | velvety               |

## **Dimensions**

| Installation depth, flush-mounted boxes | 31 mm |
|---|-------|
|---|-------|

# Installation, mounting

| Installation mode | with clamp/screw fastening |
|-------------------|----------------------------|
|-------------------|----------------------------|

## Connection

| Connection terminals     | according to IEC 60884-1        |
|--------------------------|---------------------------------|
| Connection terminals     | according to VDE 0620-1:2021-02 |
| - with plug-in terminals |                                 |

## Equipment

| With transparent product label holder | no |
|---------------------------------------|----|
|---------------------------------------|----|

## Use



# Safety

| IK protection code against mecanical impacts | 02   |
|--|--|
| Protection index IP                          | IP20   |
| Enhanced contact protection                  | according to IEC 60884-1                       |
| Enhanced contact protection                  | according to VDE 0620-1:2021-02                |
| - Enhanced contact protection                |  |
| Identification                               |  |
| Main design line                             | Berker Q.1/Q.3/Q.7/Q.9                         |
| Secondary design line(s)                     | Berker Q.1, Berker Q.3, Berker Q.7, Berker Q.9 |
| Instructions                                 |  |
| Information text                             | Insert colour-coded.                           |