



20452089



Thermostat, NO contact, with centre plate Time-controlled, Berker R.1/R.3/R.8, polar white glossy

Technical features

Functions

- with frost protection function
- with keylock
- with switchover manual/automatic mode

Controls and indicators

- operating languages adjustable: German, English, Dutch, Italian or French
- large, backlight display with text display

Main electrical features

Nominal voltage	230 V
Rated voltage	230 V AC
Frequency	50 Hz

Electric current

Switching current	8
-------------------	---

Detection

- with integrated temperature sensor

Materials

Colour of design line	polar white
Colour	polarwhite

Dimensions

Insertion depth	25 mm
-----------------	-------

Installation, mounting

Installation mode	without spreader claws
-------------------	------------------------

Connection

- with screw terminals

Settings

Room temperature setting range	5...30 °C
Hysteresis, settable	0,1...1 K

- simple programming of switching times through integrated copy function
- programme memory network failure proved
- 3 preset time programmes, individually adjustable

Equipment

Switching temperature difference	0,2 K
----------------------------------	-------

- for heating or cooling mode
- hysteresis, settable

Use

Differentiation characteristic 2 - Sales	Time-controlled
--	-----------------

Standards

General standards	EN 60730-2-7, 60730-2-9
-------------------	-------------------------

Use conditions

Energy efficiency class	I (1%)
-------------------------	--------

- temperature control range adjustable
 - temperature value can be calibrated
 - 4 temperature modes selectable
 - with thermal return via software
-

Identification

Application, usage	HVAC control
--------------------	--------------

Main design line	Berker R.1/R.3/R.8
------------------	--------------------

Secondary design line(s)	Berker R.1, Berker R.3, Berker R.8
--------------------------	------------------------------------
