



3315412089



**VGA socket outlet with screw-in lift terminals, Berker R.1/R.3/R.8, polar white glossy**

Technical features

**Connectivity**

- with straight outlet
- S-VGA compatible
- with 15pole D-subminiature jack (front)

**Frequency**

Frequency range video max. 160 MHz

**Screen**

Resolution max. 1280 x 1024 px

**Materials**

Colour of labelling	105,105,105
Colour of design line	polar white
Colour	polarwhite
RAL colour	RAL 9010 - Pure white
Material	Plastic/metal
Material for printing	ASA polar white
Surface appearance	glossy

**Installation, mounting**

Installation mode without spreader claws, for screw fastening

**Connection**

Conductor cross-section max. 1,5 mm<sup>2</sup>  
 - with screw-in lift terminals for connection to 15-core VGA cable

**Settings**

Shading parameter R1\_biaty  
 Laser parameter R1\_weiß

**Equipment**

Type of configuration Laserdruck  
 - with supporting ring

**Use**

Differentiation characteristic 3 - Sales with screw-in lift terminals

**Identification**

Application, usage Communication technology  
 Main design line Berker R.1/R.3/R.8  
 Secondary design line(s) Berker R.1, Berker R.3, Berker R.8

### Instructions

---

Information text

For connecting PCs, notebooks, etc. to display devices such as monitors (including LCD monitors) and projectors., Observe the instructions of the cable and device manufacturers for maximum VGA cable lengths!, Fränkische: "Multimedia tube" for laying pre-assembled connection cable, Art. no. 294.10.092, Installation recommendation: Kaiser: "Electronic box" for compliance with the permissible bending radii, Art. No. 1068-02 or 9062-74

---