



41092089



<b>SCHUKO socket outlet with LED orientation light enhanced contact protection, Screw-in lift terminals, Serie 1930/R.classic, polar white glossy</b>	
Technical features	
<b>Architecture</b>	
Design	according to DIN 49440
Fixing mode	flush-mounting
<b>Main electrical features</b>	
Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A
<b>Electric current</b>	
Rated current	16 A
<b>Power</b>	
Power consumption	0.25 W/0.35 VA
<b>Cover, door</b>	
Cover	Central cover plate
<b>Detection</b>	
- integrated brightness sensor that switches the orientation light on at twilight and off when there is sufficient brightness	
<b>Materials</b>	
Colour of labelling	105,105,105
Colour of design line	polar white
Colour	polarwhite
Colour	white
RAL colour	RAL 9010 - Pure white
Material	thermoplastic
Material for printing	ASA polar white
Surface appearance	glossy
<b>Dimensions</b>	
Insertion depth	32 mm
<b>Lighting control</b>	
Switch-off brightness	≈ 4 lx
Switch-on brightness	≈ 2 lx
Light intensity (white)	0,2 cd
<b>LED control</b>	
LED	white LED light, long service life of the LED

### Installation, mounting

Installation mode	with spreader claws
-------------------	---------------------

### Connection

Conductor cross-section (rigid)	max. 2,5 mm <sup>2</sup>
Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
- with screw-in lift terminals	

### Cable

- through-wiring possible, therefore also ideal for retrofitting
--

### Settings

Shading parameter	R1_biały
Laser parameter	R1_weiß

### Equipment

Type of configuration	Laserdruck
- additional benefit by combination of a socket outlet with an orientation light	

### Use

Differentiation characteristic 2 - Sales	enhanced contact protection
Differentiation characteristic 3 - Sales	Screw-in lift terminals

### Safety

IK protection code against mechanical impacts	05
Protection index IP	IP20
Enhanced contact protection	according to IEC 60884-1
Enhanced contact protection	according to VDE 0620-1:2021-02
- Enhanced contact protection	

### Identification

Main design line	Serie 1930/R.classic
Secondary design line(s)	Serie 1930, Series R.classic

### Instructions

Information text	Caution! Items with special flush-mounted insert. Centre plates with LED orientation lights are not compatible with the standard socket outlets.
- Note: When integrating this product into the Serie 1930, the 1gang frame for centre plate Ø 58 mm, order no.: 1382 0... may only be used. Installation in multiple combinations of the Serie 1930 is not possible!	