


2873



## Rotary dimmer (R, L, LED) with soft-lock, others

### Technical features

### Main electrical features

Nominal voltage	230 V
Frequency	50 Hz

### Voltage

Operating voltage	230 V AC
- voltage test possible without dismantling	

### Electric current

Control current	100 mA
-----------------	--------

### Fuse

Fine-wire fuse	T 3.15 H 250
Fuse	with spare fuse, short-circuit and overload proof (fine-wire fuse)

### Power

Dimmable conventional transformers	20...500 VA
Loss power at full load	≈ 5 W
Dimmable conventional transformers with LV-LED	20...100 VA

### Materials

Colour	not applicable
Material	Plastic/metal

### Dimensions

Axis dimension Ø	4 mm
------------------	------

### Fluorescent bulbs control

Compact fluorescent lamps	3...100 W
---------------------------	-----------

### LED control

Dimmable 230 V retrofit LED lamps	3...100 W
-----------------------------------	-----------

### Incandescent bulbs control

230 V incandescent lamps and halogen lamps	20...500 W
--	------------

### Installation, mounting

Installation mode	with spreader claws
-------------------	---------------------

### Connection

Connection cross section (solid-core)	1, 2,5 mm <sup>2</sup>
Type of load	Universal and LED Retrofit
- with terminal for base load from mains isolator	
- with plug-in terminals	

**Settings**

- basic brightness programmable

**Equipment**

- phase cut-on  
- with change-over pressure switch

**Use**

Differentiation characteristic 3 - Sales with soft-lock

**Safety**

Halogen free yes

**temperatur**

Ambient temperature 5...45 °C

**Identification**

Application, usage Light control

Secondary design line(s) Light control, House electronics

**Instructions**

Information text Possible to change fuse without removing cover.