




47861949



SCHUKO socket outlet with hinged cover for accessible construction with tactile symbol, Berker S.1/B.3/B.7, polar white matt

Technical features

Architecture

Design	according to DIN 49440
Fixing mode	flush-mounting

Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

Electric current

Rated current	16 A
---------------	------

Cover, door

Cover	Central cover plate
-	with hinged cover that falls back

Materials

Colour of design line	polar white
Colour	polarwhite
Colour	white
RAL colour	RAL 9010 - Pure white
Material	thermoplastic
Surface appearance	matt

Dimensions

Insertion depth	32 mm
-----------------	-------

Installation, mounting

Installation mode	with spreader claws
-------------------	---------------------

Connection

Conductor cross-section	1...2,5 mm ²
Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
-	with plug-in terminals

Use cases

Barrier-free building	based on DIN 18040
-----------------------	--------------------

Use

Differentiation characteristic 1 - Sales	with tactile symbol
--	---------------------

Safety

IK protection code against mechanical impacts	05
Protection index IP	IP20
- without enhanced contact protection	

Identification

Main design line	Berker S.1/B.3/B.7
Secondary design line(s)	Berker S.1, Berker B.3, Berker B.7
