



6765096086



Socket outlet with earthing pin and control LED with enhanced touch protection, Screw-in lift terminals, Berker Q.1/Q.3/Q.7/Q.9, anthracite velvety, lacquered

Technical features

Architecture

Fixing mode	flush-mounting
- 2pole + earth	

Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

Cover, door

Cover	Central cover plate
-------	---------------------

Materials

Colour of design line	anthracite
Colour	anthracite
Colour	anthracite charcoal grey
RAL colour	RAL 7021 - Black grey
Material / workmanship	lacquered
Material	duroplastic
Surface appearance	velvety

Dimensions

Insertion depth	32 mm
-----------------	-------

Installation, mounting

Installation mode	with spreader claws
-------------------	---------------------

Connection

Connection terminals	according to IEC 60884-1
- with screw-in lift terminals	

Use

Differentiation characteristic 2 - Sales	with enhanced touch protection
Differentiation characteristic 3 - Sales	Screw-in lift terminals

Safety

Enhanced contact protection	according to IEC 60884-1
- Enhanced contact protection	

Identification

Main design line	Berker Q.1/Q.3/Q.7/Q.9
Secondary design line(s)	Berker Q.1, Berker Q.3, Berker Q.7, Berker Q.9