



LED unit 230 V, for switches/push-buttons Light control, white

Technical features

Architecture

Fixing mode	flush-mounting
Technical version	230 V~, 1 mA

Controls and indicators

- for rocker push-buttons and multiple rockers push-buttons, except order no. 503404, 503808
- for change-over/intermediate switch and on/off switch, 2-pole, 10 AX

Main electrical features

Rated current	1 mA
---------------	------

Endurance

Service life of the LED	≈ 100000 h
-------------------------	------------

Materials

Colour independent of design lines	white
RAL colour	RAL 1013 - Oyster white

Equipment

- for lighting and monitoring circuit
- for series switch illuminated

Identification

Application, usage	Surface-mounted wet-room installation, Light control
Main design line	Light control
Secondary design line(s)	Light control, ACCESSORIES

Instructions

Information text	When several LED units are used, the LED current may result in malfunctioning of the relay/pulse relay. Remedy: Carry along a neutral conductor or connect a capacitor 230 V (1 µF per 10 mA LED current) in parallel with the coil.
	- Refer to the overview for the matching flush-mounted inserts.
	- these marked articles (see symbol) are only suitable for the water-protected flush-mounted installation IP44 in conjunction with the corresponding seal, frame and contact protection box (imprint "IP44").

1686

