



47631404



**SCHUKO socket outlet with hinged cover Lock - differing lockings, Berker S.1/B.3/B.7, aluminium, matt, lacquered**

Technical features

### Architecture

Design	according to DIN 49440
Fixing mode	flush-mounting

### Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

### Electric current

Rated current	16 A
---------------	------

### Cover, door

Cover	Central cover plate
-------	---------------------

### Materials

Colour of design line	aluminium
Colour	aluminium
Colour	aluminium optics
RAL colour	RAL 9006 - White aluminium
Material / workmanship	lacquered
Material	thermoplastic
Surface appearance	matt

### Installation, mounting

Installation mode	with clamp/screw fastening
-------------------	----------------------------

### Connection

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
- with plug-in terminals	

### Use

Differentiation characteristic 2 - Sales	Lock - differing lockings
--	---------------------------

### Safety

IK protection code against mechanical impacts	05
Protection index IP	IP20
- without enhanced contact protection	
- with 2 keys	

---

**Identification**

---

Application, usage	Flush-mounted wet-room installation
Main design line	Berker S.1/B.3/B.7

---

**Instructions**

---

Information text	Spare keys and other closures (max. 24) on request.
------------------	---

---

- The locks of an article do have identical lockings.  
When ordering several articles those do usually have differing lockings.

---