



47636082



SCHUKO socket outlet with hinged cover Lock - differing lockings

Technical features

Architecture

Design according to DIN 49440

Main electrical features

| | |
|-----------------|----------|
| Nominal voltage | 250 V |
| Rated voltage | 250 V AC |
| Rated current | 16 A |

Materials

| | |
|-----------------------|-------------------------|
| Colour of design line | white |
| RAL colour | RAL 1013 - Oyster white |
| Material | duroplastic |
| Surface appearance | velvety |

Connection

| | |
|--------------------------|---------------------------------|
| Connection terminals | according to IEC 60884-1 |
| Connection terminals | according to VDE 0620-1:2021-02 |
| - with plug-in terminals | |

Use

| | |
|--|---------------------------|
| Differentiation characteristic 2 - Sales | Lock - differing lockings |
|--|---------------------------|

Safety

| | |
|---------------------|------|
| Protection index IP | IP20 |
| - with 2 keys | |

Identification

| | |
|--------------------------|--|
| Application, usage | Flush-mounted wet-room installation |
| Secondary design line(s) | Berker Q.1, Berker Q.3, Berker Q.7, Berker Q.9 |

Instructions

| | |
|---|---|
| Information text | Spare keys and other closures (max. 24) on request. |
| - The locks of an article do have identical lockings. When ordering several articles those do usually have differing lockings. | |