



47637004



SCHUKO socket outlet with hinged cover Lock - differing lockings, Berker K.5

Technical features

Architecture

Design	according to DIN 49440
Fixing mode	flush-mounting

Connectivity

Type of USB port	other
------------------	-------

Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

Electric current

Rated current	16 A
---------------	------

Cover, door

Cover	Central cover plate
-------	---------------------

Materials

Colour of design line	stainless steel
Colour	Stainless steel
Colour	stainless steel optics
RAL colour	RAL 9022 - Pearl light grey
Material / workmanship	lacquered
Material	thermoplastic
Surface appearance	mat

Dimensions

Installation depth, flush-mounted boxes	31 mm
-----------------------------------------	-------

Installation, mounting

Installation mode	with clamp/screw fastening
-------------------	----------------------------

Connection

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
- with plug-in terminals	

Use

Differentiation characteristic 2 - Sales	Lock - differing lockings
------------------------------------------	---------------------------

Safety

IK protection code against mechanical impacts	05
Protection index IP	IP20

- without enhanced contact protection
- with 2 keys

Identification

Application, usage	Flush-mounted wet-room installation
Main design line	Berker K.5

Instructions

Information text	Spare keys and other closures (max. 24) on request.
------------------	-----------------------------------------------------

- The locks of an article do have identical lockings.
When ordering several articles those do usually have differing lockings.
- Only suitable for splash-protected IP44 flush-mounted installation when used in conjunction with sealing set (order no. 10107200).
