



47631606





SCHUKO socket outlet with hinged cover Lock - differing lockings, Berker S.1/B.3/B.7, anthracite, matt

Technical features

AICHILECTULE	Arc	hite	cture
--------------	-----	------	-------

Design	according to DIN 49440
Fixing mode	flush-mounting

Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

Electric current

Rated current	16 A
---------------	------

Cover, door

Materials

Colour of design line	anthracite
Colour	anthracite
Colour	anthracite charcoal grey
RAL colour	RAL 7021 - Black grey
Material	thermoplastic
Surface appearance	matt

Installation, mounting

Installation mode	with clamp/screw fastening
-------------------	----------------------------

Connection

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02

- with plug-in terminals

Use

Differentiation characteristic 2 - Sales	Lock - differing lockings
--	---------------------------

Safety

IK protection code against mecanical impacts	05
Protection index IP	IP20
- without enhanced contact protection	

- with 2 keys

Identification

Application, usage	Flush-mounted wet-room installation
Main design line	Berker S.1/B.3/B.7
Secondary design line(s)	Berker B.3, Berker B.7



Instructions

Information text

Spare keys and other closures (max. 24) on request.

- The locks of an article do have identical lockings. When ordering several articles those do usually have differing lockings.