



6768116084



**Socket outlet with earthing pin and hinged cover with enhanced touch protection, with lock - differing lockings, Berker Q.1/Q.3/Q.7/Q.9, aluminium, matt, lacquered**

Technical features

#### Architecture

Fixing mode	flush-mounting
- 2pole + earth	

#### Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

#### Cover, door

Cover	Central cover plate
-------	---------------------

#### Materials

Colour of design line	aluminium
Colour	aluminium
Colour	aluminium optics
RAL colour	RAL 9006 - White aluminium
Material / workmanship	lacquered
Material	thermoplastic
Surface appearance	velvety

#### Installation, mounting

Installation mode	with spreader claws
-------------------	---------------------

#### Connection

Connection terminals	according to IEC 60884-1
----------------------	--------------------------

#### Use

Differentiation characteristic 1 - Sales	with enhanced touch protection
Differentiation characteristic 2 - Sales	with lock - differing lockings

#### Safety

IK protection code against mechanical impacts	05
- without enhanced contact protection	

#### Identification

Main design line	Berker Q.1/Q.3/Q.7/Q.9
------------------	------------------------

#### Instructions

Information text	Spare keys and other closures (max. 24) on request.
- Only suitable for splash-protected IP44 flush-mounted installation when used in conjunction with sealing set (order no. 10107200).	