



47637003



**SCHUKO socket outlet with hinged cover Lock - differing lockings, Berker K.5, aluminium, matt, lacquered**

Technical features

**Architecture**

Design	according to DIN 49440
Fixing mode	flush-mounting

**Connectivity**

Type of USB port	other
------------------	-------

**Main electrical features**

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

**Electric current**

Rated current	16 A
---------------	------

**Cover, door**

Cover	Central cover plate
-------	---------------------

**Materials**

Colour of design line	aluminium
Colour	aluminium
Colour	aluminium optics
RAL colour	RAL 9006 - White aluminium
Material / workmanship	lacquered
Material	thermoplastic
Surface appearance	matt

**Dimensions**

Installation depth, flush-mounted boxes	31 mm
---	-------

**Installation, mounting**

Installation mode	with clamp/screw fastening
-------------------	----------------------------

**Connection**

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
- with plug-in terminals	

**Use**

Differentiation characteristic 2 - Sales	Lock - differing lockings
--	---------------------------

---

**Safety**

---

IK protection code against mechanical impacts	05
Protection index IP	IP20

---

- without enhanced contact protection
- with 2 keys

---

**Identification**

---

Application, usage	Flush-mounted wet-room installation
Main design line	Berker K.5

---

**Instructions**

---

Information text	Spare keys and other closures (max. 24) on request.
------------------	---

---

- The locks of an article do have identical lockings.  
When ordering several articles those do usually have differing lockings.
- Only suitable for splash-protected IP44 flush-mounted installation when used in conjunction with sealing set (order no. 10107200).

---