



47248982



**SCHUKO socket outlet with hinged cover with enhanced touch protection, Berker S.1/B.3/B.7, white glossy**

Technical features

**Architecture**

Design	according to DIN 49440
Fixing mode	flush-mounting

**Main electrical features**

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

**Electric current**

Rated current	16 A
---------------	------

**Cover, door**

Cover	Central cover plate
-------	---------------------

**Materials**

Colour of design line	white
Colour	white
RAL colour	RAL 1013 - Oyster white
Material	thermoplastic
Surface appearance	glossy

**Installation, mounting**

Installation mode	for flush-mounted and hollow-wall mounting
-------------------	--

**Connection**

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
- with plug-in terminals	

**Equipment**

With transparent product label holder	no
---------------------------------------	----

**Use**

Differentiation characteristic 2 - Sales	with enhanced touch protection
--	--------------------------------

**Safety**

IK protection code against mechanical impacts	02
Enhanced contact protection	according to VDE 0620-1:2021-02
- enhanced contact protection VDE 0620-1:2021-02	

**Identification**

Main design line	Berker S.1/B.3/B.7
------------------	--------------------

**Instructions**

---

- Only suitable for splash-protected IP44 flush-mounted installation when used in conjunction with the corresponding sealing set.
-