



6768117001



**with lock - differing lockings, Berker K.5, bronze matt, lacquered**

Technical features

**Architecture**

Fixing mode	flush-mounting
- 2pole + earth	

**Connectivity**

Type of USB port	other
------------------	-------

**Main electrical features**

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

**Cover, door**

Cover	Central cover plate
-------	---------------------

**Materials**

Colour	bronze
Colour	hellbronze optics
RAL colour	RAL 1035 - Pearl beige
Material	thermoplastic
Surface appearance	matt

**Dimensions**

Installation depth, flush-mounted boxes	31 mm
---	-------

**Installation, mounting**

Installation mode	with spreader claws
-------------------	---------------------

**Connection**

Connection terminals	according to IEC 60884-1
----------------------	--------------------------

**Use**

Differentiation characteristic 2 - Sales	with lock - differing lockings
--	--------------------------------

**Safety**

IK protection code against mechanical impacts	05
- without enhanced contact protection	

**Identification**

Main design line	Berker K.5
------------------	------------

**Instructions**

---

Information text Spare keys and other closures (max. 24) on request.

- Only suitable for splash-protected IP44 flush-mounted installation when used in conjunction with the corresponding sealing set.
-