



6765117001



**with lock - differing lockings, with screw-in lift terminals, Berker K.5, bronze, aluminium, anodised**

#### Technical features

#### Architecture

Fixing mode	flush-mounting
- 2pole + earth	

#### Connectivity

Type of USB port	other
------------------	-------

#### Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

#### Cover, door

Cover	Central cover plate
-------	---------------------

#### Materials

Colour	bronze
Colour	hellbronze optics
RAL colour	RAL 1035 - Pearl beige
Material	thermoplastic
Surface appearance	matt

#### Dimensions

Installation depth, flush-mounted boxes	31 mm
---	-------

#### Installation, mounting

Installation mode	with spreader claws
-------------------	---------------------

#### Connection

Connection terminals	according to IEC 60884-1
----------------------	--------------------------

#### Use

Differentiation characteristic 2 - Sales	with lock - differing lockings
Differentiation characteristic 3 - Sales	with screw-in lift terminals

#### Safety

IK protection code against mechanical impacts	05
- without enhanced contact protection	

#### Identification

Main design line	Berker K.5
------------------	------------

#### Instructions

---

Information text	Spare keys and other closures (max. 24) on request.
------------------	---

---

- Only suitable for splash-protected IP44 flush-mounted installation when used in conjunction with the corresponding sealing set.

---