


296110



Universal rotary dimmer (R, L, C, LED) with soft-lock, Light control

Technical features

Functions

- bulb-preserving soft startup

Controls and indicators

- with soft-lock

Main electrical features

Nominal voltage 230 V

Frequency 50/60 Hz

Voltage

Operating voltage 230 V AC

- voltage test possible without dismantling

Fuse

Fuse short-circuit and overload proof (electronic fuse)

Power

Dimmable conventional transformers 20...420 VA

Loss power at full load ≈ 4 W

Electronic transformers 20...420 W

Measurement

Extension unit input with extension unit input for push-button (NO contact) with single-surface operation, with input for extension units insert for universal rotary dimmer

Materials

Colour not applicable

Material Plastic/metal

Dimensions

Insertion depth 24 mm

Axis dimension Ø 4 mm

LED control

Dimmable 230 V retrofit LED lamps 3...100 W

Incandescent bulbs control

230 V incandescent lamps and halogen lamps 20...420 W

Installation, mounting

Installation mode with spreader claws

Connection

| | |
|-------------------------|----------------------------|
| Type of load | Universal and LED Retrofit |
| Conductor cross-section | 0,5...4 mm ² |
| - with screw terminals | |

Scope of delivery

- with incremental encoder

Equipment

- phase cut-on, cut-off or LED phase cut-on according to load type, self-learning
- with brightness memory

Use

| | |
|--|----------------|
| Differentiation characteristic 3 - Sales | with soft-lock |
|--|----------------|

Safety

| | |
|--------------|-----|
| Halogen free | yes |
|--------------|-----|

Identification

| | |
|--------------------|---------------|
| Application, usage | Light control |
| Main design line | Light control |