product sheet 47231606



47231606

SCHUKO socket outlet with enhanced touch protection, Berker S.1/B.3/B.7, anthracite, matt

Technical features

Design	according to DIN 4944
Fixing mode	flush-mountin
Main electrical features	
Nominal voltage	250
Rated voltage	250 V A
Frequency	50/60 H
Rated current	16
Electric current	
Rated current	16.
Cover, door	
Cover	Central cover plat
Materials	
Colour of design line	anthracit
Colour	anthracit
Colour	anthracite charcoal grey
RAL colour	RAL 7021 - Black gre
Material	thermoplasti
Surface appearance	ma
Dimensions	
Insertion depth	32 mr
Installation, mounting	
Installation mode	with spreader claw
Connection	
Connection terminals	according to IEC 60884-
Connection terminals	according to VDE 0620-1:2021-0
- with plug-in terminals	
- with plug-in terminals Use Differentiation characteristic 2 - Sales	with enhanced touch protectio
Use Differentiation characteristic 2 - Sales	with enhanced touch protectio
Use	
Use Differentiation characteristic 2 - Sales Safety IK protection code against mecanical impacts	0
Use Differentiation characteristic 2 - Sales Safety	with enhanced touch protectio 0 IP2 according to IEC 60884-



Identification

Main design lineBerker S.1/B.3/B.7Secondary design line(s)Berker S.1, Berker B.3, Berker B.7