



41231404



SCHUKO socket outlet with enhanced touch protection, Screw-in lift terminals, Berker S.1/B.3/B.7, aluminium, matt, lacquered

Technical features

Architecture

| | |
|-------------|------------------------|
| Design | according to DIN 49440 |
| Fixing mode | flush-mounting |

Main electrical features

| | |
|-----------------|----------|
| Nominal voltage | 250 V |
| Rated voltage | 250 V AC |
| Frequency | 50/60 Hz |
| Rated current | 16 A |

Electric current

| | |
|---------------|------|
| Rated current | 16 A |
|---------------|------|

Cover, door

| | |
|-------|---------------------|
| Cover | Central cover plate |
|-------|---------------------|

Materials

| | |
|------------------------|----------------------------|
| Colour of design line | aluminium |
| Colour | aluminium |
| Colour | aluminium optics |
| RAL colour | RAL 9006 - White aluminium |
| Material / workmanship | lacquered |
| Material | thermoplastic |
| Surface appearance | matt |

Dimensions

| | |
|-----------------|-------|
| Insertion depth | 32 mm |
|-----------------|-------|

Installation, mounting

| | |
|-------------------|---------------------|
| Installation mode | with spreader claws |
|-------------------|---------------------|

Connection

| | |
|--------------------------------|---------------------------------|
| Connection terminals | according to IEC 60884-1 |
| Connection terminals | according to VDE 0620-1:2021-02 |
| - with screw-in lift terminals | |

Use

| | |
|--|--------------------------------|
| Differentiation characteristic 2 - Sales | with enhanced touch protection |
| Differentiation characteristic 3 - Sales | Screw-in lift terminals |

Safety

| | |
|---|---------------------------------|
| IK protection code against mechanical impacts | 05 |
| Protection index IP | IP20 |
| Enhanced contact protection | according to IEC 60884-1 |
| Enhanced contact protection | according to VDE 0620-1:2021-02 |
| - Enhanced contact protection | |

Identification

| | |
|--------------------------|------------------------------------|
| Main design line | Berker S.1/B.3/B.7 |
| Secondary design line(s) | Berker S.1, Berker B.3, Berker B.7 |