


41438912



**SCHUKO socket outlet with screw-in lift terminals, Berker S.1/B.3/B.7, red glossy**

Technical features

**Architecture**

Design according to DIN 49440

Fixing mode flush-mounting

**Connectivity**

Type of USB port other

**Main electrical features**

Nominal voltage 250 V

Rated voltage 250 V AC

Frequency 50/60 Hz

Rated current 16 A

**Electric current**

Rated current 16 A

**Cover, door**

Cover Central cover plate

**Materials**

Design lines special colours red

Colour red

Colour red

RAL colour RAL 3003 - Ruby red

Material duroplastic

Surface appearance glossy

**Dimensions**

Insertion depth 32 mm

Installation depth, flush-mounted boxes 31 mm

**Installation, mounting**

Installation mode with spreader claws

**Connection**

Connection terminals according to IEC 60884-1

Connection terminals according to VDE 0620-1:2021-02

- with screw-in lift terminals

**Use**

Differentiation characteristic 3 - Sales with screw-in lift terminals

**Safety**

---

IK protection code against mechanical impacts	02
Protection index IP	IP20
- without enhanced contact protection	

---

**Identification**

---

Main design line	Berker S.1/B.3/B.7
Secondary design line(s)	Berker S.1, Berker B.3, Berker B.7

---

**Instructions**

---

Information text	Insert colour-coded.
------------------	----------------------

---