



47438922



SCHUKO socket outlet with "EDV" imprint Berker S.1/B.3/B.7, red glossy

Technical features

AICHILECTULE	Arc	hite	cture
--------------	-----	------	-------

Design	according to DIN 49440
Fixing mode	flush-mounting
Technical version	Imprint "EDV"

Connectivity

Type of USB port	other
------------------	-------

Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Rated current	16 A

Electric current

Rated current	16 A

Cover, door

Cover	Central cover plate
-------	---------------------

Materials

red
red
red
RAL 3003 - Ruby red
duroplastic
glossy

Dimensions

Insertion depth	32 mm
Installation depth, flush-mounted boxes	31 mm

Installation, mounting

Installation mode	with spreader claws
installation mode	with spreader claws

Connection

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
- with plug-in terminals	

Safety

IK protection code against mecanical impacts	02
Protection index IP	IP20
- without enhanced contact protection	



Identification

Main design line	Berker S.1/B.3/B.7
Secondary design line(s)	Berker S.1, Berker B.3, Berker B.7
Instructions	
Information text	Insert colour-coded.