





47501913



## SCHUKO socket outlet with "SV" imprint Labelling field, Berker S.1/B.3/B.7, green matt

### Technical features

#### Architecture

|                   |                        |
|-------------------|------------------------|
| Design            | according to DIN 49440 |
| Fixing mode       | flush-mounting         |
| Technical version | Imprint "SV"           |

#### Main electrical features

|                 |          |
|-----------------|----------|
| Nominal voltage | 250 V    |
| Rated voltage   | 250 V AC |
| Frequency       | 50/60 Hz |
| Rated current   | 16 A     |

#### Electric current

|               |      |
|---------------|------|
| Rated current | 16 A |
|---------------|------|

#### Cover, door

|       |                     |
|-------|---------------------|
| Cover | Central cover plate |
|-------|---------------------|

#### Materials

|                              |                       |
|------------------------------|-----------------------|
| Design lines special colours | green                 |
| Colour                       | green                 |
| Colour                       | green                 |
| RAL colour                   | RAL 6029 - Mint green |
| Material                     | thermoplastic         |
| Surface appearance           | matt                  |

#### Dimensions

|                 |       |
|-----------------|-------|
| Insertion depth | 32 mm |
|-----------------|-------|

#### Installation, mounting

|                   |                     |
|-------------------|---------------------|
| Installation mode | with spreader claws |
|-------------------|---------------------|

#### Connection

|                          |                                 |
|--------------------------|---------------------------------|
| Connection terminals     | according to IEC 60884-1        |
| Connection terminals     | according to VDE 0620-1:2021-02 |
| - with plug-in terminals |                                 |

#### Use

|                                          |                 |
|------------------------------------------|-----------------|
| Differentiation characteristic 1 - Sales | Labelling field |
|------------------------------------------|-----------------|

#### Safety

|                                               |      |
|-----------------------------------------------|------|
| IK protection code against mechanical impacts | 05   |
| Protection index IP                           | IP20 |
| - without enhanced contact protection         |      |

**Identification**

|                          |                                    |
|--------------------------|------------------------------------|
| Main design line         | Berker S.1/B.3/B.7                 |
| Secondary design line(s) | Berker S.1, Berker B.3, Berker B.7 |

**Instructions**

|                  |                                                                                |
|------------------|--------------------------------------------------------------------------------|
| Information text | Insert colour-coded., Labelling field height arranged for P-touch strips 6 mm. |
|------------------|--------------------------------------------------------------------------------|