


47501913



SCHUKO socket outlet with "SV" imprint Labelling field, Berker S.1/B.3/B.7, green matt

Technical features

Architecture

| | |
|-------------------|------------------------|
| Design | according to DIN 49440 |
| Fixing mode | flush-mounting |
| Technical version | Imprint "SV" |

Main electrical features

| | |
|-----------------|----------|
| Nominal voltage | 250 V |
| Rated voltage | 250 V AC |
| Frequency | 50/60 Hz |
| Rated current | 16 A |

Electric current

| | |
|---------------|------|
| Rated current | 16 A |
|---------------|------|

Cover, door

| | |
|-------|---------------------|
| Cover | Central cover plate |
|-------|---------------------|

Materials

| | |
|------------------------------|-----------------------|
| Design lines special colours | green |
| Colour | green |
| Colour | green |
| RAL colour | RAL 6029 - Mint green |
| Material | thermoplastic |
| Surface appearance | matt |

Dimensions

| | |
|-----------------|-------|
| Insertion depth | 32 mm |
|-----------------|-------|

Installation, mounting

| | |
|-------------------|---------------------|
| Installation mode | with spreader claws |
|-------------------|---------------------|

Connection

| | |
|--------------------------|---------------------------------|
| Connection terminals | according to IEC 60884-1 |
| Connection terminals | according to VDE 0620-1:2021-02 |
| - with plug-in terminals | |

Use

| | |
|--|-----------------|
| Differentiation characteristic 1 - Sales | Labelling field |
|--|-----------------|

Safety

| | |
|---|------|
| IK protection code against mechanical impacts | 05 |
| Protection index IP | IP20 |
| - without enhanced contact protection | |

Identification

| | |
|--------------------------|------------------------------------|
| Main design line | Berker S.1/B.3/B.7 |
| Secondary design line(s) | Berker S.1, Berker B.3, Berker B.7 |

Instructions

| | |
|------------------|--|
| Information text | Insert colour-coded., Labelling field height arranged for P-touch strips 6 mm. |
|------------------|--|
