



47299909 |

Double SCHUKO socket outlet with cover pl	late enhanced	contact protection,	Berker S.1, pola	ar white matt
---	---------------	---------------------	------------------	---------------

_				•		
ם ו	nh.	nıc	പ	fea	tı ır	-Δc

_			
Δrc	hit	ecti	IIFE

Design	according to DIN 49440
Fixing mode	flush-mounting

Connectivity

Type of USB port	other

Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

Electric current

Rated current	16 A

Cover, door

Materials

Colour of design line	polar white	
Colour	polarwhite	
Colour	white	
RAL colour	RAL 9010 - Pure white	
Material	thermoplas	
Surface appearance	matt	
rrace appearance	matt	

Dimensions

Installation depth, flush-mounted boxes	31 mm
Assembling height	22 mm

Installation, mounting

For installation in 1gang wall boxes	according to DIN 49073-1
Installation mode	with spreader claws

Connection

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
- with plug-in terminals	

Use

Differentiation characteristic 2 - Sales	enhanced contact protection
--	-----------------------------



Safety

IK protection code against mecanical impacts	05
Protection index IP	IP20
Enhanced contact protection	according to IEC 60884-1
Enhanced contact protection	according to VDE 0620-1:2021-02
- Enhanced contact protection	
Identification	
Main design line	Berker S.1