



Double SCHUKO socket outlet with frame enhanced contact protection, Berker B.1, aluminium/anthracite matt, aluminium anodised

Technical features

Architecture

Design	according to DIN 49440
Fixing mode	flush-mounting

Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50 Hz
Rated current	16 A

Electric current

Rated current	16 A
---------------	------

Cover, door

Cover	Central cover plate
-------	---------------------

Materials

Colour of design line	aluminium/anthracite
Colour	aluminium optics
RAL colour	RAL 9006 - White aluminium
Material / workmanship	aluminium, anodised
Material	Aluminium
Surface appearance	matt

Dimensions

Assembling height	22 mm
-------------------	-------

Installation, mounting

For installation in 1gang wall boxes	according to DIN 49073-1
--------------------------------------	--------------------------

Connection

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
- with plug-in terminals	

Use

Differentiation characteristic 2 - Sales	enhanced contact protection
--	-----------------------------

Safety

IK protection code against mechanical impacts	07
Protection index IP	IP20
Enhanced contact protection	according to IEC 60884-1
Enhanced contact protection	according to VDE 0620-1:2021-02
- Enhanced contact protection	

Identification

Main design line	Berker B.1
Secondary design line(s)	Berker B.3
