


41668989



**Socket outlet with earthing contact USA/CANADA NEMA 5-15 R with screw terminals, Berker S.1/B.3/B.7, polar white glossy**

Technical features

#### Architecture

Fixing mode	flush-mounting
- 2pole + earth	

#### Main electrical features

Nominal voltage	125 V
Rated voltage	125 V AC
Frequency	50/60 Hz
Rated current	15 A

#### Cover, door

Cover	Central cover plate
-------	---------------------

#### Materials

Colour of design line	polar white
Colour	polarwhite
Colour	white
RAL colour	RAL 9010 - Pure white
Material	thermoplastic
Surface appearance	glossy

#### Dimensions

Insertion depth	19 mm
-----------------	-------

#### Installation, mounting

Installation mode	without spreader claws, for screw fastening
-------------------	---

#### Connection

Conductor cross-section (rigid)	max. 2 x 4 mm <sup>2</sup>
- with screw terminals	

#### Use

Differentiation characteristic 3 - Sales	with screw terminals
--	----------------------

#### Standards

Standard	NEMA 5-15 R
----------	-------------

#### Safety

IK protection code against mechanical impacts	05
- without enhanced contact protection	

#### Identification

Main design line	Berker S.1/B.3/B.7
Secondary design line(s)	Berker S.1, Berker B.3, Berker B.7

**Instructions**

---

Information text

Not UL-certified.

---