



Change-over switch Light control

Technical features

Architecture

Type of control unit	single rocker
Fixing mode	flush-mounting

Functions

Switching angle	3,5 °
-----------------	-------

Configuration

- Off/change-over

Controls and indicators

- No

Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC

Electric current

Switching current	10 AX (100 W Self Ballasted Lamp (SBL))
-------------------	---

Materials

Material	Plastic/metal
Surface appearance	matt

Dimensions

Depth	42 mm
Insertion depth	31 mm
Height	71 mm
Width	71 mm

Installation, mounting

Installation mode	with spreader claws, for screw fastening
-------------------	--

Connection

Connection terminals	according to IEC 60669-1
Connection terminals	according to VDE 0632-1
Type of connection	Quickconnect
- with plug-in terminals	

Equipment

- for lighting and monitoring circuit

Safety

Protection index IP	IP20
Impact strength	IK07

Identification

Application, usage	HVAC control, Light control
Appliance switch type	No
Main design line	Light control

Instructions

Information text	spreader claws, insulated to the supporting ring, self-resetting
------------------	--

- A control change-over switch is shown here as an example. With 2-pole and 3-pole control on/off switches, other rocker switches and neon lamp units are required.