



303650



Change-over switch for installation in hollow walls Light control

Technical features

Architecture

| | |
|----------------------|------------------|
| Type of control unit | single rocker |
| Fixing mode | surface-mounting |

Functions

| | |
|-----------------|-------|
| Switching angle | 3,5 ° |
|-----------------|-------|

Configuration

- Off/change-over

Controls and indicators

- No

Main electrical features

| | |
|-----------------|----------|
| Nominal voltage | 250 V |
| Rated voltage | 250 V AC |

Electric current

| | |
|-------------------|---|
| Switching current | 10 AX (100 W Self Ballasted Lamp (SBL)) |
|-------------------|---|

Materials

| | |
|--------------------|---------------|
| Material | Plastic/metal |
| Surface appearance | matt |

Dimensions

| | |
|-----------------|---------|
| Depth | 41,6 mm |
| Insertion depth | 19,5 mm |
| Height | 71 mm |
| Width | 71 mm |

Installation, mounting

| | |
|-------------------|---|
| Installation mode | without spreader claws, low installation depth, for screw fastening |
|-------------------|---|

Connection

| | |
|--------------------------|--------------------------|
| Connection terminals | according to IEC 60669-1 |
| Connection terminals | according to VDE 0632-1 |
| Type of connection | Quickconnect |
| - with plug-in terminals | |

Equipment

- for lighting and monitoring circuit

Safety

| | |
|---------------------|------|
| Protection index IP | IP20 |
|---------------------|------|

Identification

| | |
|--------------------|-----------------------------|
| Application, usage | Light control, HVAC control |
| Main design line | Light control |
