



503101



Push-button, NO contact Light control

Technical features

Architecture

| | |
|----------------------|----------------------------|
| Type of control unit | rocker |
| Technical version | 2 separate signal contacts |

Functions

| | |
|-----------------|-------|
| Switching angle | 3,5 ° |
|-----------------|-------|

Configuration

- NO, with 2 separate signalling contacts

Main electrical features

| | |
|-----------------|----------|
| Nominal voltage | 250 V |
| Rated voltage | 250 V AC |

Electric current

| | |
|---------------------------|------|
| Momentary-contact current | 10 A |
|---------------------------|------|

Materials

| | |
|----------|---------------|
| Material | Plastic/metal |
|----------|---------------|

Dimensions

| | |
|-----------------|---------|
| Depth | 41,6 mm |
| Insertion depth | 31 mm |
| Height | 71 mm |
| Width | 71 mm |

Installation, mounting

| | |
|-------------------|---------------------|
| Installation mode | with spreader claws |
|-------------------|---------------------|

Connection

| | |
|---------------------------------|--------------------------|
| Conductor cross-section (rigid) | max. 2,5 mm ² |
| Connection terminals | according to IEC 60669-1 |
| Connection terminals | according to VDE 0632-1 |
| - with plug-in terminals | |

Equipment

| | |
|---------------------------------------|---|
| Quantity of NO contacts | 1 |
| - for lighting and monitoring circuit | |

Safety

| | |
|---------------------|------|
| Protection index IP | IP20 |
|---------------------|------|

Identification

| | |
|--------------------|---------------|
| Application, usage | Light control |
| Main design line | Light control |

Instructions

| | |
|------------------|--|
| Information text | spreader claws, insulated to the supporting ring, self-resetting |
|------------------|--|