product sheet 61503404



61503404



• • •	
Configuration	
- Normally open contact	
Main electrical features	
Rated voltage	250 V .
Electric current	
Momentary-contact current	1(
Materials	
Material	Plastic/me
Dimensions	
Depth	42 n
Height	71 n
Width	71 n
Installation, mounting	
Installation mode	low installation depth, without spreader cla
Connection	
Connection Connection terminals	according to IEC 6066
Connection terminals	according to VDE 063
Connection terminals Connection terminals	according to VDE 063
Connection terminals Connection terminals Type of connection	according to VDE 063
Connection terminals Connection terminals Type of connection - with screw terminals	according to VDE 063
Connection terminals Connection terminals Type of connection - with screw terminals Equipment	according to VDE 063
Connection terminals Connection terminals Type of connection - with screw terminals Equipment - for lighting and monitoring circuit	according to VDE 063 Screw connect
Connection terminals Connection terminals Type of connection - with screw terminals Equipment - for lighting and monitoring circuit Safety	according to IEC 60669 according to VDE 0633 Screw connection
Connection terminals Connection terminals Type of connection - with screw terminals Equipment - for lighting and monitoring circuit Safety Protection index IP	according to VDE 063 Screw connect

Group push-button for installation in hollow-walls Modul-inserts