



503808



## Series push-button, 2 change-over contacts Light control

Technical features

### Architecture

|                      |                          |
|----------------------|--------------------------|
| Type of control unit | double rocker            |
| Technical version    | isolated input terminals |

### Configuration

- double change-over contact, usable as NC or NO with separate input terminals

### Main electrical features

|                 |          |
|-----------------|----------|
| Nominal voltage | 250 V    |
| Rated voltage   | 250 V AC |

### Electric current

|                           |      |
|---------------------------|------|
| Momentary-contact current | 10 A |
|---------------------------|------|

### Materials

|          |               |
|----------|---------------|
| Material | Plastic/metal |
|----------|---------------|

### Dimensions

|        |         |
|--------|---------|
| Depth  | 41,6 mm |
| Height | 71 mm   |
| Width  | 71 mm   |

### Installation, mounting

|                   |                     |
|-------------------|---------------------|
| Installation mode | with spreader claws |
|-------------------|---------------------|

### Connection

|                      |                          |
|----------------------|--------------------------|
| Connection terminals | according to IEC 60669-1 |
| Connection terminals | according to VDE 0632-1  |
| Type of connection   | Screw connection         |
| -                    | with screw terminals     |

### Equipment

- for illumination

### Safety

|                     |      |
|---------------------|------|
| Protection index IP | IP20 |
|---------------------|------|

### Identification

|                    |               |
|--------------------|---------------|
| Application, usage | Light control |
| Main design line   | Light control |

### Instructions

|                  |  |
|------------------|--|
| Information text | spreader claws, insulated to the supporting ring, self-resetting |
|------------------|--|