



85105100



## KNX radio switch actuator for plugs Electronics platform, polar white matt

### Technical features

#### Architecture

Fixing mode	surface-mounting
-------------	------------------

#### Functions

- ETS additional functions: +6 scenes, operating mode on/off, forced control, status display
- reset function (to factory setting)
- Repeat function can be activated to increase the radio range
- easy additional functions: +6 scenes
- scene opening via KNX radio appliances
- scene saving lockable
- quicklink functions: switching, 2 scenes, time switching, NO contact push-button

#### Controls and indicators

- with manual operation on/off
- with configuration and function button

#### Connectivity

Bus system radio frequent	no
Bus system LON	no
Bus system Powernet	no
Radio protocol	KNX Radio
Receiver category	2

#### Main electrical features

Frequency	50 Hz
-----------	-------

#### Electric current

Switching current	16 A
-------------------	------

#### Frequency

Radio reception frequency	868,3 MHz
---------------------------	-----------

#### Power

Output power	3680 W
Conventional transformers	1600 VA
Electronic transformers and dual-mode transformers	1200 W
C-load	no

#### Measurement

Relative humidity (without condensation)	0...65 % (without condensation)
--	---------------------------------

#### Materials

Colour of design line	polar white
Surface appearance	matt

### Dimensions

Depth	77 mm
Assembling height	41 mm
Height	98 mm
Width	54 mm

### Fluorescent bulbs control

Fluorescent lamps	28 x 36 W, max. 120 µF
-------------------	------------------------

### LED control

LED	with configuration and function LEDs, with control LED for On/Off
-----	---

### Incandescent bulbs control

230 V incandescent lamps and halogen lamps	2300 W
--	--------

### Connection

- integration in the KNX radio/TP gateway, surface-mounted, into the KNX TP system

### Settings

- toolless quicklink configuration using buttons and LED display

### Scope of delivery

Bus connection included	no
-------------------------	----

### Equipment

Number of outputs	1
Number of quicklink links	max. 20 transmitter/receiver
Transmitter duty cycle	1 %
Different phases connectable	no

### Use conditions

Operating temperature	0...45 °C
- low intrinsic energy requirement	

### Identification

Application, usage	KNX radio - actuators
Product family	product family: output
Main design line	Electronics platform