



85475100



IP30

## KNX radio universal dim actuator 1gang flush-mounted Electronics platform, light grey

### Technical features

#### Functions

- ETS additional functions: +6 scenes, operating mode on/off, dimming value, forced control, status display, brightness display, repeater function
- reset function (to factory setting)
- scene opening via KNX radio appliances
- scene saving lockable
- quicklink functions: dimming, 2 scenes, time switching, NO contact push-button
- bulb-preserving soft startup

#### Controls and indicators

- with manual operation on/off, brighter/darker
- with configuration and function button

#### Connectivity

Radio protocol	KNX Radio
Receiver category	2

#### Fuse

Fuse	short-circuit and overload proof (electronic fuse)
------	--

#### Frequency

Radio reception frequency	868,3 MHz
---------------------------	-----------

#### Power

Conventional transformers	20...200 VA
Electronic transformers	20...200 W

#### Measurement

Relative humidity (without condensation)	0...65 % (without condensation)
--	---------------------------------

#### Materials

Colour independent of design lines	light grey
------------------------------------	------------

#### Dimensions

Dimensions (Ø x H)	56 x 38 mm
Diameter	56 mm
Height	46,6 mm

#### LED control

LED	with control LED for On/Off, with configuration and function LEDs
-----	---

#### Incandescent bulbs control

230 V incandescent lamps and halogen lamps	20...200 W
--	------------

#### Connection

Type of load	universal
<ul style="list-style-type: none"><li>- with screw-in lift terminals</li><li>- integration in the KNX radio/TP gateway, surface-mounted, into the KNX TP system</li></ul>	

#### Settings

<ul style="list-style-type: none"><li>- toolless quicklink configuration using buttons and LED display</li></ul>
--

#### Equipment

Number of quicklink links	max. 20 transmitter/receiver
Modular expandability	no
Product type:	Product type: Dimming actuator
Transmitter duty cycle	1 %
<ul style="list-style-type: none"><li>- phase cut-on or cut-off according to load type, self-learning</li></ul>	

#### Use conditions

Operating temperature	0...45 °C
<ul style="list-style-type: none"><li>- low intrinsic energy requirement</li></ul>	

#### Identification

Application, usage	KNX radio - actuators
Product family	product family: output
Main design line	Electronics platform