


294810



Time relay insert Light control

Technical features

Controls and indicators

- is switched off when actuated in the switched-on state

Main electrical features

| | |
|-----------------|----------|
| Nominal voltage | 240 V |
| Frequency | 50/60 Hz |

Electric current

| | |
|---------------|-----|
| Rated current | 6 A |
|---------------|-----|

Fuse

| | |
|------|--|
| Fuse | short-circuit and overload proof (fine-wire fuse), with spare fuse |
|------|--|

Power

| | |
|---------------------------|---------|
| Conventional transformers | 1000 VA |
| Electronic transformers | 1500 W |

Measurement

| | |
|----------------------|--|
| Extension unit input | with extension unit input for push-button (NO contact) |
|----------------------|--|

Materials

| | |
|----------|----------------|
| Colour | not applicable |
| Material | Plastic/metal |

Dimensions

| | |
|------------------|---------|
| Insertion depth | 32,5 mm |
| Axis dimension Ø | 4 mm |

Lighting control

| | |
|-----------------|--------|
| - uncompensated | 500 VA |
|-----------------|--------|

Fluorescent bulbs control

| | |
|--|---------|
| Fluorescent lamps in duo circuit | 1000 VA |
| Fluorescent lamps parallel compensated | 150 VA |

LED control

| | |
|-----|----------------------|
| LED | with red control LED |
|-----|----------------------|

Incandescent bulbs control

| | |
|--------------------------|--------|
| 230 V incandescent lamps | 1500 W |
| 230 V halogen lamps | 300 W |

Installation, mounting

Installation mode with spreader claws

Settings

Delay time, adjustable ≈ 1 mn...1 h

Equipment

-
- very low noise
 - electronic timer with on/off pressure switch
-

Identification

Application, usage Light control

Main design line Light control
