



85605100



IP50

## KNX radio hand-held transmitter 2-channel with labelling field, Electronics platform, polar white/grey, glossy/matt

### Technical features

#### Functions

- ETS additional functions: +6 scenes, operating mode on/off, push-button, status display, dimming value
- reset function (to factory setting)
- quicklink functions: switching, dimming, blind, 2 scenes, time switching, NO contact push-button, memory

#### Controls and indicators

- with side locking buttons
- with configuration button

#### Connectivity

Radio protocol	KNX Radio
Receiver category	2

#### Frequency

Radio transmission frequency	868,3 MHz
------------------------------	-----------

#### Power

Radio transmission power	< 10 mW
--------------------------	---------

#### Measurement

Relative humidity (without condensation)	0...65 % (without condensation)
--	---------------------------------

#### Battery

Battery service life [years]	≈ 5
- with 2 x lithium coin cell battery 3 V type: CR 2430	

#### Materials

Colour independent of design lines	polar white/grey
Material	thermoplastic
Surface appearance	glossy/matt

#### Dimensions

Length	83 mm
Height	84,2 mm
Width	46,5 mm

#### LED control

LED	with transmission status and battery status LED, red/green/orange, with configuration LED
-----	---

#### Connection

- integration in the KNX radio/TP gateway, surface-mounted, into the KNX TP system

#### Equipment

Number of radio channels	2
Number of quicklink links	max. 20 transmitter/receiver
Transmitter duty cycle	1 %

#### Use

Differentiation characteristic 1 - Sales	with labelling field
--	----------------------

#### Safety

- with keyring

#### Use conditions

Operating temperature	-10...45 °C
- low intrinsic energy requirement	

#### Identification

Application, usage	KNX radio- operating systems
Main design line	Electronics platform