



85608100



**KNX radio hand-held transmitter 18-channel with labelling field, Electronics platform, white/dark blue**

Technical features

**Functions**

- ETS additional functions: +6 scenes, operating mode on/off, push-button, status display, dimming value
- reset function (to factory setting)
- quicklink functions: switching, dimming, blind, 2 scenes, time switching, NO contact push-button, memory

**Connectivity**

Radio protocol	KNX Radio
Receiver category	2

**Frequency**

Radio transmission frequency	868,3 MHz
------------------------------	-----------

**Power**

Radio transmission power	< 10 mW
--------------------------	---------

**Measurement**

Relative humidity (without condensation)	0...65 % (without condensation)
--	---------------------------------

**Battery**

Battery service life [years]	≈ 5
- with 2 x lithium coin cell battery 3 V type: CR 2430	

**Materials**

Colour independent of design lines	white/dark blue
Material	thermoplastic
Surface appearance	other

**Dimensions**

Length	133,6 mm
Height	134 mm
Width	50,2 mm

**LED control**

LED	with transmission status and battery status LED, red/green/orange, with configuration LED
-----	---

**Connection**

- integration in the KNX radio/TP gateway, surface-mounted, into the KNX TP system

**Equipment**

Number of radio channels	18
Number of quicklink links	max. 20 transmitter/receiver
Transmitter duty cycle	1 %
- with movement and actuation-dependent labelling field illumination	
- with channel group slide switch	

**Use**

---

Differentiation characteristic 1 - Sales with labelling field

---

**Use conditions**

---

Operating temperature 0...45 °C

---

- low intrinsic energy requirement

---

**Identification**

---

Application, usage KNX radio- operating systems

---

Main design line Electronics platform

---