





286110



Universal rotary dimmer (R, L, C) with soft-lock, Light control, others

Technical features

Functions

- bulb-preserving soft startup

Controls and indicators

- with soft-lock

Main electrical features

Nominal voltage	230 V
Frequency	50/60 Hz

Voltage

Operating voltage	230 V AC
- voltage test possible without dismantling	

Fuse

Fuse	short-circuit and overload proof (electronic fuse)
------	--

Power

Dimmable conventional transformers	50...420 VA
connected load	50...420 W/VA
Loss power at full load	≈ 5 W
Electronic transformers	50...420 W

Measurement

Extension unit input	with input for extension units insert for universal rotary dimmer
----------------------	---

Materials

Colour	not applicable
Material	Plastic/metal

Dimensions

Axis dimension Ø	4 mm
------------------	------

Incandescent bulbs control

230 V incandescent lamps and halogen lamps	50...420 W
--	------------

Installation, mounting

Installation mode	with spreader claws
-------------------	---------------------

Connection

Type of load	universal
- with plug-in terminals	

Scope of delivery

- with incremental encoder

Equipment

- phase cut-on or cut-off according to load type, self-learning
- very low noise
- with brightness memory

Use

Differentiation characteristic 3 - Sales with soft-lock

Safety

Halogen free yes

Identification

Application, usage Light control

Release issue 2

Main design line Light control

Instructions

Information text Trouble-free operation will be obtained only with Berker TronicÂ® transformers.