


286110



Universal rotary dimmer (R, L, C) with soft-lock, Light control, others

Technical features

Functions

- bulb-preserving soft startup

Controls and indicators

- with soft-lock

Main electrical features

Nominal voltage 230 V

Frequency 50/60 Hz

Voltage

Operating voltage 230 V AC

- voltage test possible without dismantling

Fuse

Fuse short-circuit and overload proof (electronic fuse)

Power

Dimmable conventional transformers 50...420 VA

connected load 50...420 W/VA

Loss power at full load ≈ 5 W

Electronic transformers 50...420 W

Measurement

Extension unit input with input for extension units insert for universal rotary dimmer

Materials

Colour not applicable

Material Plastic/metal

Dimensions

Axis dimension Ø 4 mm

Incandescent bulbs control

230 V incandescent lamps and halogen lamps 50...420 W

Installation, mounting

Installation mode with spreader claws

Connection

Type of load universal

- with plug-in terminals

Scope of delivery

- with incremental encoder
-

Equipment

- phase cut-on or cut-off according to load type, self-learning
 - very low noise
 - with brightness memory
-

Use

Differentiation characteristic 3 - Sales with soft-lock

Safety

Halogen free yes

Identification

Application, usage Light control

Release issue 2

Main design line Light control

Instructions

Information text Trouble-free operation will be obtained only with
Berker TronicÂ® transformers.
