


286110



## Universal rotary dimmer (R, L, C) with soft-lock, Light control, others

### Technical features

### Functions

- bulb-preserving soft startup

### Controls and indicators

- with soft-lock

### Main electrical features

Nominal voltage 230 V

Frequency 50/60 Hz

### Voltage

Operating voltage 230 V AC

- voltage test possible without dismantling

### Fuse

Fuse short-circuit and overload proof (electronic fuse)

### Power

Dimmable conventional transformers 50...420 VA

connected load 50...420 W/VA

Loss power at full load ≈ 5 W

Electronic transformers 50...420 W

### Measurement

Extension unit input with input for extension units insert for universal rotary dimmer

### Materials

Colour not applicable

Material Plastic/metal

### Dimensions

Axis dimension Ø 4 mm

### Incandescent bulbs control

230 V incandescent lamps and halogen lamps 50...420 W

### Installation, mounting

Installation mode with spreader claws

### Connection

Type of load universal

- with plug-in terminals

---

**Scope of delivery**

- with incremental encoder
- 

**Equipment**

- phase cut-on or cut-off according to load type, self-learning
  - very low noise
  - with brightness memory
- 

**Use**

Differentiation characteristic 3 - Sales with soft-lock

---

**Safety**

Halogen free yes

---

**Identification**

Application, usage Light control

---

Release issue 2

---

Main design line Light control

---

**Instructions**

Information text Trouble-free operation will be obtained only with  
Berker TronicÂ® transformers.

---