



Neon lamp unit with N terminal Light control, orange

Technical features

Architecture

Technical version	230 V~, 0.4 mA
-------------------	----------------

Controls and indicators

- for rocker push-buttons and multiple rockers push-buttons, except order no. 503404, 503808
- for change-over/intermediate switch and on/off switch, 2-pole, 10 AX

Main electrical features

Rated current	0,4 mA
---------------	--------

Materials

Colour independent of design lines	orange
------------------------------------	--------

Dimensions

Insertion depth	13 mm
-----------------	-------

Equipment

- for lighting and monitoring circuit
- for series switch illuminated

Identification

Application, usage	Light control
Main design line	Light control
Secondary design line(s)	Light control, ACCESSORIES

Instructions

Information text	<p>When several neon lamp units are used, the lamp current may result in malfunctioning of the relay/pulse relay.</p> <p>Remedy: Carry along a neutral conductor or connect a capacitor 230 V (1 µF per 10 mA neon lamp current) in parallel with the coil.</p> <ul style="list-style-type: none"> - Refer to the overview for the matching flush-mounted inserts. - these marked articles (see symbol) are only suitable for the water-protected flush-mounted installation IP44 in conjunction with the corresponding seal, frame and contact protection box (imprint "IP44").
------------------	--

167504

